



Per Viti for Thread	Dimensions (mm)				Test load daN	h after test mm	kgs/1K
	D mm	d mm	e mm	h mm			
M6	17.00	6.50	2.40	0.80	320	0.60	3.60
M8	20.00	8.50	2.80	0.95	400	0.70	5.60
M10	23.00	10.50	3.20	1.05	600	0.80	7.90
M12	26.00	12.50	4.00	1.30	1150	1.00	13.00
M14	29.00	15.00	4.80	1.30	1300	0.90	18.00
M16	33.00	17.00	4.80	1.40	1250	1.10	24.00
M18	37.00	19.00	6.00	1.52	2100	1.20	35.00
M20	41.00	21.00	6.00	1.85	2100	1.40	45.00
M22	45.00	23.00	7.20	1.67	2700	1.40	60.00
M24	50.00	25.00	7.20	1.84	2900	1.60	81.00
M27	56.00	28.50	8.00	1.80	3600	1.60	115.00
M30	60.00	32.00	8.80	2.30	4200	1.80	135.00
M33	64.00	35.00	10.00	2.57	6300	2.00	170.00
M36	68.00	38.00	10.00	2.50	6200	2.00	190.00
M39	72.00	41.00	10.00	2.45	5500	2.20	210.00
M42	76.00	44.00	10.00	3.20	5700	2.40	223.00
M45	80.00	47.00	10.00	2.75	6500	2.50	240.00
M48	85.00	50.00	10.00	2.85	5700	2.60	280.00
M52	90.00	54.00	12.00	3.55	7500	2.80	370.00
M56	95.00	58.00	12.00	3.22	7200	3.00	405.00
M60	100.00	62.00	12.00	3.25	7000	3.00	441.00